



The SuperVault iTANK SERIES

The SuperVault iTank has been re-designed and certified as a rectangular 'obround' shape to cater for much tighter space requirements, both indoors and outdoors. Speed to market for unmanned fuel stops, and less 'sunk' cost makes an attractive case.

This precision engineered fuel tank is 4-hour fire-rated and is recommended due to its fire protective safety for commercial sectors. The SuperVault tank offers elite fire-rated, projectile resistance and impact resistance technology which makes it the safest and most durable tank in the world.

SPECIFICATIONS

- Environmentally Secure
- Compliant with International Tank Approvals
- Multi Hazard Tested
- Emergency Venting
- Superior Thermal Efficiency
- Made in New Zealand
- Interstitial Monitoring Capability
- Maximum Paint Protection
- Capable of Storing Many Hazardous Liquids
- Internal Tank Lining for Special Applications
- Easily Transportable when Empty
- 30 Year Warranty

Model	Description	Capacity (litres)	Width (mm)	Length (mm)	Height (mm)	Weight (empty kg)
SViT 215-13,000	SuperVault 4 hour fire rated iTank	13000	2440	6060	1500	
SViT 215-19,800	SuperVault 4 hour fire rated iTank	19800	2440	9100	1500	
SViT 215-26,900	SuperVault 4 hour fire rated iTank	27000	2440	12160	1500	
SViT 315-16,700	SuperVault 4 hour fire rated iTank	16700	3000	6060	1500	
SViT 315-25,500	SuperVault 4 hour fire rated iTank	25500	3000	9100	1500	
SViT 315-34,600	SuperVault 4 hour fire rated iTank	34600	3000	12160	1500	
SViT 218-16,700	SuperVault 4 hour fire rated iTank	16700	2440	6060	1800	
SViT 218-25,700	SuperVault 4 hour fire rated iTank	25700	2440	9100	1800	
SViT 218-34,658	SuperVault 4 hour fire rated iTank	34600	2440	12160	1800	
SViT 318-21,900	SuperVault 4 hour fire rated iTank	22000	3000	6060	1800	
SViT 318-33,600	SuperVault 4 hour fire rated iTank	33600	3000	9100	1800	
SViT 318-45,312	SuperVault 4 hour fire rated iTank	45300	3000	121600	1800	
SViT 227-27,394	SuperVault 4 hour fire rated iTank	27300	2440	6060	2700	
SViT 227-41,703	SuperVault 4 hour fire rated iTank	41700	2440	9100	2700	
SViT 227-56,600	SuperVault 4 hour fire rated iTank	56500	2440	12160	2700	
SViT 227-67,700	SuperVault 4 hour fire rated iTank	67600	2440	14478	2700	
SViT 327-35,600	SuperVault 4 hour fire rated iTank	35600	3000	6060	2700	
SViT 327-54,630	SuperVault 4 hour fire rated iTank	54600	3000	9100	2700	
SViT 327-73,630	SuperVault 4 hour fire rated iTank	73600	3000	12160	2700	
SViT 327-88,000	SuperVault 4 hour fire rated iTank	88900	3000	14478	2700	